

FDM Machine/Material Reference



Printer

Printer	Build Envelope (XYZ)	Cartridge Or Canister Volume	External Dim. (WxDxH)	Layer Thickness (Z-Height)
F170™	25.4 x 25.4 x 25.4 cm (10 x 10 x 10 in.)	60 or 90 cu in.	86.4 x 71.1 x 162.6 cm (34 x 28 x 64 in.)	0.330 mm (0.013 in.), 0.254 mm (0.010 in.), 0.178 mm (0.007 in.), 0.127 mm (0.005 in.)
F370™	35.6 x 25.4 x 35.6 cm (14 x 10 x 14 in.)	60 or 90 cu in.	86.4 x 71.1 x 162.6 cm (34 x 28 x 64 in.)	0.330 mm (0.013 in.), 0.254 mm (0.010 in.), 0.178 mm (0.007 in.), 0.127 mm (0.005 in.)
F770™	100 x 61 x 61 cm (39.4 x 24 x 24 in.)	200 cu in.	175 x 124 x 196 cm (69 x 49 x 77 in.)	0.330 mm (0.013 in.), 0.254 mm (0.010 in.), 0.178 mm (0.007 in.)
F190™CR	30.5 cm x 25.4 cm x 30.5 cm (12 x 10 x 12 in.)	60 or 90 cu in.	86.4 x 71.1 x 162.6 cm (34 x 28 x 64 in.)	0.330 mm (0.013 in.), 0.254 mm (0.010 in.), 0.178 mm (0.007 in.), 0.127 mm (0.005 in.)
F370®CR	35.6 cm x 25.4 cm x 35.6 cm (14 x 10 x 14 in.)	60 or 90 cu in.	86.4 x 71.1 x 162.6 cm (34 x 28 x 64 in.)	0.330 mm (0.013 in.), 0.254 mm (0.010 in.), 0.178 mm (0.007 in.), 0.127 mm (0.005 in.)
Fortus 450mc™	40.6 x 35.6 x 40.6 cm (16 x 14 x 16 in.)	92 cu in., 184 cu in., 500 cu in.	127 x 90.17 x 198.4 cm (50 x 35.5 x 76.5 in.)	0.330 mm (0.013 in.), 0.254 mm (0.010 in.), 0.178 mm (0.007 in.), 0.127 mm (0.005 in.)
F900™	91.4 x 60.7 x 91.4 cm (36 x 24 x 36 in.)	92 cu in., 184 cu in., 500 cu in.	277.2 x 168.3 x 202.7 cm (109.1 x 66.3 x 79.8 in.)	0.508 mm (0.020 in.), 0.330 mm (0.013 in.), 0.254 mm (0.010 in.), 0.178 mm (0.007 in.), 0.127 mm (0.005 in.)

Material Classification (refer to material datasheets for specific properties and colors)

Standard Plastics

ABS-M30™

ABS-M30i™

ABS-ESD7™

ASA

FDM HIPS

PLA

Engineering Plastics

ABS-CF10

Addigy® PA6/66-GF20 FR LS

Diran™ 410MF07

FDM™ Nylon 6

FDM™ Nylon 12

FDM® Nylon-CF10

FDM™ TPU 92A

Kimya PC-FR

PC

PC-ABS

PC-ISO™

High-Performance Plastics

Antero™ 800NA

Antero™ 840CN03

FDM™ Nylon 12 CF

PPSF

ULTEM™ 9085 resin

ULTEM™ 1010 resin

VICTREX AM™ 200

ST-130™

FDM Machine/Material Reference

Support Material

Material	F170	F190CR	F370	F370CR	F770	Fortus 450mc	Stratasys F900
ABS-M30	QSR	QSR	QSR	QSR	SR30	SR30, SR35	SR30, SR35
ABS-M30i	-	-	-	-	-	SR30, SR35	SR30, SR35
ABS-ESD7	-	-	QSR	QSR	-	SR30, SR35	SR30, SR35
ASA	QSR	QSR	QSR	QSR	SR30	SR30, SR35	SR30, SR35
PLA	PLA	-	PLA	-	-	-	SR110
ABS-CF10	QSR	QSR	QSR	QSR	-	-	-
PC-ABS	-	-	QSR	QSR	-	SR110	SR110
PC	-	-	-	-	-	SR100, PC BASS*	SR100, PC BASS*
PC-ISO	-	-	-	-	-	PC BASS*	PC BASS*
FDM Nylon 6	-	-	-	-	-	-	SR110
FDM Nylon 12	-	-	-	-	-	SR110	SR110
FDM TPU 92A	QSR	QSR	QSR	QSR	-	-	-
Diran 410MF07	-	-	SUP4000B	SUP4000B	-	-	-
Antero 800NA	-	-	-	-	-	SUP8000B	SUP8000B
Antero 840CN03	-	-	-	-	-	SUP8000B	SUP8000B
FDM Nylon 12CF	-	-	-	-	-	SR110	SR110
FDM Nylon-CF10	-	QSR	-	QSR	-	-	-
ST-130	-	-	-	-	-	ST130S	ST130S
ULTEM™ 9085 resin	-	-	-	-	-	SUP8500B	SUP8500B
ULTEM™ 1010 resin	-	-	-	-	-	SUP9000B	SUP9000B
ULTEM™ 9085 resin CG	-	-	-	-	-	SUP8500B	SUP8500B
ULTEM™ 1010 resin CG	-	-	-	-	-	SUP9000B	SUP9000B
PPSF	-	-	-	-	-	-	PPSF BASS*
Addigy PA6/66-GF20 FR LS	-	-	-	-	-	SUP4000B	-
Kimya PC-FR	-	-	-	-	-	SR100	-
Victrex AM 200	-	-	-	-	-	SR100	-
FDM HIPS	-	-	-	-	-	SUP1500B	-

* BASS stands for Breakaway Support System

HEADQUARTERS

7665 Commerce Way,
Eden Prairie, MN 55344
+1 800 801 6491 (US Toll Free)
+1 952 937-3000 (Intl)
+1 952 937-0070 (Fax)

1 Holtzman St., Science Park,
PO Box 2496
Rehovot 76124, Israel
+972 74 745 4000
+972 74 745 5000 (Fax)

STRATASYS.COM

ISO 9001:2015 Certified