



UltiMaker S7 Product data sheet

Best-in-class reliability

We took everything our users loved about the award winning UltiMaker S5, and we made it even better. The UltiMaker S7 can be trusted to do its job, giving you the freedom to do yours. The inductive sensor-enabled bed leveling of the S7 ensures a perfect first layer and the integrated air manager maintains the build volume at an optimally regulated temperature. Additionally, run-out and fan bracket sensors will pause your print and notify you if you run out of filament or if there is a clog that causes your print head to flood.

Ultimate connectivity

The UltiMaker S7 is your gateway to the entire UltiMaker platform. Access all the tools you need to start 3D printing – Manage and monitor your prints securely with the UltiMaker Digital Factory, improve your 3D printing knowledge with e-learning courses on the UltiMaker Academy, and choose from hundreds of materials and plugins using the UltiMaker Marketplace.

- Easy setup and monitoring: Start printing quickly with a simple first-time user experience. Including NFC material recognition and a high-resolution internal camera
- Access to the UltiMaker platform: Seamless integration with the extensive UltiMaker platform. Including software, materials, and hardware
- Environmental control: The integrated air manager filters out up to 95% of UFPs while also keeping the build chamber temperature carefully regulated
- Advanced active leveling: Reliable first-layer adhesion enables unattended use without manual leveling
- Wide material choice: Use almost any material with our open filament system, including composites
- Large build volume: Scale up with bigger parts or batch production
- Network connectivity: Print via Wi-Fi, LAN, cloud, or USB
- UltiMaker Essentials: Access to security-assessed software
 with remote printing, user management, and e-learning
- Flexible build plate: The PEI-coated build plate makes for reliable print adhesion and removal. A sensor also assures your build plate will always be in place before printing

The UltiMaker platform

	Ъ	
Ľ		

3D printers that simply work

Our award-winning 3D printers are robust, reliable, and easy to use. They deliver quality parts time and again. Designed and tested to run 24/7, they allow you to achieve the results you need more quickly and easily.



Software ready for Industry 4.0

Trusted by millions of users across 14 languages, UltiMaker Cura integrates with any workflow through UltiMaker Marketplace plugins. Then scale production and digital distribution with UltiMaker Digital Factory.



Material choice like never before

UltiMaker offers the widest material choice on the market. Through our Material Alliance, choose the perfect filament for your application – from advanced polymers to carbon fiber composites.



Support dedicated to your success

Wherever you are in the world, UltiMaker support is close by. Our global network of service partners offer professional installation, training, and maintenance in your language and time zone.



Request a quote today at <u>ultimaker.com/quote/request</u>

UltiMaker S7 specifications

Printer and printing properties	Technology	Fused filament fabrication (FFF)
	Print head	Dual extrusion print head with auto-nozzle lifting system and swappable print cores
	Build volume (XYZ)	330 x 240 x 300 mm (13 x 9.4 x 11.8 in)
	Layer resolution	0.25 mm nozzle: 150 - 60 micron 0.4 mm nozzle: 200 - 20 micron 0.6 mm nozzle: 300 - 20 micron 0.8 mm nozzle: 600 - 20 micron
	XYZ resolution	6.9, 6.9, 2.5 micron
	Build speed	< 24 mm³/s
	Build plate	PEI coated flexible build plate (20 - 140 °C)
	Air manager	EPA filter - Independently tested according to UL2904 (Standard Method for Testing and Assessing Particle and Chemical Emissions from 3D Printers) with UltiMaker materials and corresponding Cura print profiles.
	Nozzle diameter	0.4 mm (included) 0.25 mm, 0.6 mm, 0.8 mm (sold separately)
	Operating sound	< 50 dBA
	Connectivity	Wi-Fi (2.4GHz + 5GHz), LAN, USB port
Physical dimensions	Dimensions (with spool holder)	495 x 585 x 800 mm (19.5 x 23 x 31,5 in)
	Net weight	29.1 kg (64.2 lbs)
Software	Free supplied software	UltiMaker Personal (for individuals – includes UltiMaker Cura) UltiMaker Essentials (for organizations – includes UltiMaker Cura Enterprise) Find our full range of enterprise plans at ultimaker.com/software
	Supported OS	MacOS, Windows, and Linux
Warranty	Warranty period	12 months

Compatible accessories



Material Station Simplify and automate material handling

Compatible materials



Print core BB Quick-swap nozzles for build and water-soluble support materials. Available in 0.25, 0.4, and 0.8 mm



Print core CC Hardened steel nozzle for printing abrasive glass and carbon fiber composites. Available in 0.4 and 0.6 mm



PVA Removal Station Remove water-soluble PVA support material up to 4X faster

Unlock a wide range of applications with complete material choice. Use UltiMaker materials, any third-party filament, or access material profiles from leading brands. Choose from these materials and more.

Wear resistance

UltiMaker Nylon

• Igus iglidur® I150

BASF Forward AM

XSTRAND™ GF30-PA6

• UltiMaker PP

Easy	to	print
------	----	-------

• UltiMaker PLA

- UltiMaker Tough PLA
- UltiMaker PETG

Flame retardant

- EDS safe
- Kimya ABS ESD
- Jabil PET G 0800 ESD





• Covestro Addigy® F1030 FR

• Ensinger PC FR Natural

Mechanical strength

• UltiMaker ABS

• UltiMaker CPE

• UltiMaker PC

Reinforced composites Support • UltiMaker PVA

- Covestro Addigy® F1030 FR
 AquaSys ® 120

Flexibility

- UltiMaker TPU 95A
- Estane® 3D TPU F94A

UltiMaker

- Lehvoss LUVOCOM 3F PAHT® 9825 NT
- Lehvoss LUVOCOM 3F PAHT 9826 NT

Heat resistance

• UltiMaker CPF+

- UltiMaker Breakaway





UltiMaker S7 Pro Bundle Product data sheet

Best-in-class reliability

We took everything our users loved about the award winning UltiMaker S5, and we made it even better. The UltiMaker S7 can be trusted to do its job, giving you the freedom to do yours. The inductive sensor-enabled bed leveling of the S7 ensures a perfect first layer and the integrated air manager maintains the build volume at an optimally regulated temperature. Additionally, run-out and fan bracket sensors will pause your print and notify you if you run out of filament or if there is a clog that causes your print head to flood.

Ultimate connectivity

The UltiMaker S7 is your gateway to the entire UltiMaker platform. Access all the tools you need to start 3D printing – Manage and monitor your prints securely with the UltiMaker Digital Factory, improve your 3D printing knowledge with e-learning courses on the UltiMaker Academy, and choose from hundreds of materials and plugins using the UltiMaker Marketplace.

- Easy setup and monitoring: Start printing quickly with a simple first-time user experience. Including NFC material recognition and a high-resolution internal camera
- Access to the UltiMaker platform: Seamless integration with the extensive UltiMaker platform. Including software, materials, and hardware
- Environmental control: The integrated air manager filters out up to 95% of UFPs while also keeping the build chamber temperature carefully regulated
- Advanced active leveling: Reliable first-layer adhesion enables unattended use without manual leveling
- Flexible material choice: The 6 materials bays can be used to automatically switch and continuously print with a huge range of materials
- Large build volume: Scale up with bigger parts or batch production
- Network connectivity: Print via Wi-Fi, LAN, cloud, or USB
- UltiMaker Essentials: Access to security-assessed software
 with remote printing, user management, and e-learning
- Flexible build plate: The PEI-coated build plate makes for reliable print adhesion and removal. A sensor also assures your build plate will always be in place before printing

The UltiMaker platform

3D printers that simply work

Our award-winning 3D printers are robust, reliable, and easy to use. They deliver quality parts time and again. Designed and tested to run 24/7, they allow you to achieve the results you need more quickly and easily.



Software ready for Industry 4.0

Trusted by millions of users across 14 languages, UltiMaker Cura integrates with any workflow through UltiMaker Marketplace plugins. Then scale production and digital distribution with UltiMaker Digital Factory.



Material choice like never before

UltiMaker offers the widest material choice on the market. Through our Material Alliance, choose the perfect filament for your application – from advanced polymers to carbon fiber composites.



Support dedicated to your success

Wherever you are in the world, UltiMaker support is close by. Our global network of service partners offer professional installation, training, and maintenance in your language and time zone.





UltiMaker S7 Pro specifications

Printer and printing properties	Technology	Fused filament fabrication (FFF)	
	Print head	Dual extrusion print head with auto-nozzle lifting system and swappable print cores	
	Build volume (XYZ)	330 x 240 x 300 mm (13 x 9.4 x 11.8 in)	
	Layer resolution	0.25 mm nozzle: 150 - 60 micron 0.4 mm nozzle: 200 - 20 micron 0.6 mm nozzle: 300 - 20 micron 0.8 mm nozzle: 600 - 20 micron	
	XYZ resolution	6.9, 6.9, 2.5 micron	
	Build speed	< 24 mm³/s	
	Build plate	PEI coated flexible build plate (20 - 140 °C)	
	Feeder type	Dual-geared, abrasion-resistant	
	Spool bays	6 with NFC recognition	
	Air manager	EPA filter - Independently tested according to UL2904 (Standard Method for Testing and Assessing Particle and Chemical Emissions from 3D Printers) with UltiMaker materials and corresponding Cura print profiles.	
	Nozzle diameter	0.4 mm (included) 0.25 mm, 0.6 mm, 0.8 mm (sold separately)	
	Operating sound	< 50 dBA	
	Connectivity	Wi-Fi (2.4GHz + 5GHz), LAN, USB port	
hysical dimensions	Dimensions	495 x 500 x 1190 mm (19.5 x 19.7 x 46.9 in)	
	Net weight	46.7 kg (103 lbs)	
oftware	Free supplied software	UltiMaker Personal (for individuals – includes UltiMaker Cura) UltiMaker Essentials (for organizations – includes UltiMaker Cura Enterprise) Find our full range of enterprise plans at ultimaker.com/software	
	Supported OS	MacOS, Windows, and Linux	
Warranty	Warranty period	12 months	

Compatible accessories



Cleaning filament Ideal for keeping your UltiMaker print cores in optimal condition

Compatible materials



Print core BB Quick-swap nozzles for build and water-soluble support materials. Available in 0.25, 0.4, and 0.8 mm



Print core CC Hardened steel nozzle for printing abrasive glass and carbon fiber composites. Available in 0.4 and 0.6 mm

Heat resistance

• UltiMaker CPE+

Lehvoss LUVOCOM 3F



PVA Removal Station Remove water-soluble PVA support material up to 4X faster

Flexibility

• UltiMaker TPU 95A

• Estane® 3D TPU F94A

Unlock a wide range of applications with complete material choice. Use UltiMaker materials, any third-party filament, or access material profiles from leading brands. Choose from these materials and more.

Wear resistance

UltiMaker Nylon

• UltiMaker PP

Easy	to	print
Lusy		print

- UltiMaker PLA
- UltiMaker Tough PLA
- UltiMaker PETG

- EDS safe • Kimya ABS ESD
- Jabil PET G 0800 ESD



Mechanical strength

• UltiMaker ABS

• UltiMaker PC

• UltiMaker CPE

• Igus iglidur® I150 PAHT® 9825 NT Lehvoss LUVOCOM 3F **PAHT 9826 NT Reinforced composites** Support

 BASF Forward AM UltiMaker PVA • UltiMaker Breakaway

- Covestro Addigy® F1030 FR XSTRAND[™] GF30-PA6

Covestro Addigy® F1030 FR AquaSys ® 120

UltiMaker





